

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>C09K 7/02</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 97/05212</b> <b>(43) International Publication Date:</b> 13 February 1997 (13.02.97)
<b>(21) International Application Number:</b> PCT/IB95/00731 <b>(22) International Filing Date:</b> 5 September 1995 (05.09.95) <b>(30) Priority Data:</b> PCT/IB95/00587 26 July 1995 (26.07.95) WO <i>(34) Countries for which the regional or international application was filed:</i> CH et al. <b>(71)(72) Applicant and Inventor:</b> URQUHART, John, Charles [GB/CH]; 21 Granary Street, Burghead, Elgin IV30 2UJ (GB).		<b>(81) Designated States:</b> AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TT, UA, UG, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i>
<b>(54) Title:</b> POTASSIUM SILICATE DRILLING FLUID  <b>(57) Abstract</b>  An aqueous drilling fluid for use in drilling through reactive clays and shales and other soft formations e.g. chalk, contains in addition to typical polymeric agents for fluid loss control and rheological control, a stabiliser consisting essentially of a range of exclusively potassium silicates i.e. containing silica and potassium oxide in various ratios, but no bentonite or barite or other solids weighting material and is free of brine solutions commonly used in prior art drilling fluids.		

Best Available Copy

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

**POTASSIUM SILICATE DRILLING FLUID**Field of the invention

This invention relates to drilling and more particularly to the drilling fluids used in the drilling of wells in the search for oil, gas and water or in the completion of oil, gas and water wells.

Background of the invention

A particular problem is encountered while drilling through reactive clays and shales and other soft formations e.g. chalk. Typical water based drilling fluids may cause reactive clays and shales to swell which can cause severe drilling problems which can lead to the abandonment of the well. Oil based drilling fluids are used to prevent clays and shales swelling, but are a source of environmental problems.

Background art

US-A-3 640 343 proposed the use of a water-soluble sodium silicate in the stabilisation of hard shaly earth formations by forcing fluids containing said silicate deep into the shaly earth formations. Numerous other patents refer to use of alkali metal salts as components having adjuvant or auxiliary additive functionality in drilling fluids and amongst these the following may be referred to as illustrative of the art:

US-A-2 146 693, US-A-2 165 823/4, US-A-3 259 189,  
US-A-3 738 437, US-A-3 679 001, US-A-4 988 450,  
US-A-4 525 285, US-A-5 211 250; SU-A-1 199 786.

It is generally the case that the use of alkali metal salts in the known drilling fluids involves relatively small amounts in conjunction with many other components such as solids weighting agents, thickeners, rheology modifiers, and miscellaneous organic shale stabilisers often of a polyfunctional polymeric species.

Objects of the invention

An object of the present invention is to obviate or mitigate the aforesaid disadvantages of known drilling problems in drilling operations carried upon reactive clays

and shales and other soft formations. A further object is to provide a drilling fluid useful in drilling operations in soft formations.

Summary of the invention

5 According to the present invention there is provided an aqueous drilling fluid containing a proportion of polymeric agents for fluid loss control and rheological control, and an amount of alkali metal silicate characterised in that the alkali metal silicate content consists essentially of a  
10 range of potassium silicates i.e. containing silica and potassium oxide in various ratios.

The most preferred fluid consists essentially of water containing from 28 to 35% by weight of potassium silicate wherein the silica ( $\text{SiO}_2$ ) content is from 20 to 40% by  
15 weight and the potassium oxide ( $\text{K}_2\text{O}$ ) content is from 8 to 15% by weight.

The polymeric agents for fluid loss control and rheological control may be selected from cellulose based polymers, e.g. carboxymethyl cellulose and xanthan gums but  
20 this preference does not exclude the use of other polymeric species having equivalent properties. Preferred amounts include from 3 to 6  $\text{kg/m}^3$  of viscosity modifier and from 1 to 3  $\text{kg/m}^3$  of fluid loss inhibitor. Suitable polymeric materials are commercially available as proprietary  
25 materials for the purposes stated.

The most preferred fluids exhibit viscosities in the range of 35 - 50 mPas at 20 C (as measured on a Fann 35 rheometer).

Fluids of this invention surprisingly exhibit fluid  
30 loss of below 4 mls on the API standard fluid loss test wherein drilling fluid is placed in the standard filter press cup at a pressure of 100 psi ( $6.89 \times 10^5$  Pa) for 30 minutes. That test provides an indication of the life expectancy or circulation loss performance to be obtained in  
35 use of the fluid in a porous formation. In fact the preferred fluids of this invention exhibit zero fluid loss in this standard test which is a result which was hitherto inconceivable at the levels of polymer additives utilised in

this invention. Typical drilling fluids forming the state of the art till now exhibit fluid loss of no better than about 8 to 10 mls in such a test and that is attainable only through use of from 20 kg/m<sup>3</sup> of polymer and 75 kg/m<sup>3</sup> of bentonite.

There is therefore provided by this invention a reliable method of drilling and consolidating a borehole in a shale, chalk or similar soft formation wherein during a drilling operation there is introduced an aqueous drilling fluid comprising an amount of alkali metal silicate wherein the alkali metal silicate content consists essentially of a range of potassium silicates, and a proportion of polymeric agents for fluid loss control and rheological control thereby providing for substantially zero fluid loss and a viscosity of from 35 - 50 mPas at 20 C.

Best mode for carrying out the invention

An example of the preferred compositions of drilling fluid according to the invention is now described in order to more clearly illustrate the nature of the invention.

Example

Component	% by weight
Potassium Silicate	29.75
SiO <sub>2</sub> content	21.30
K <sub>2</sub> O content	8.45
Water	70
pH	11.2 - 11.4
Fluid enhancing additives:	
Viscosity Modifier	3 - 6 kg/m <sup>3</sup>
Fluid Loss Inhibitor	1 - 3 kg/m <sup>3</sup>

The fluid just described is made by forming a suitable potassium silicate solution within the ranges specified herein e.g. as above of about 30% by weight potassium silicate of a preselected mole ratio of SiO<sub>2</sub> to K<sub>2</sub>O and about 70 % by weight water, and slowly adding the selected viscosity modifier and fluid loss inhibitor agents through a mixing hopper into a tank of the potassium silicate solution. The physical properties of the drilling fluid

such as viscosity and especially the density can be selectively varied by introducing potassium silicate of differing mole ratio as a powder e.g. obtainable by spray drying of a selected potassium silicate solution.

5

#### Industrial applicability

The introduction of a potassium silicate drilling fluid according to the invention during the drilling operation offers significant advantages which are attributable to the unexpectedly advantageous properties arising from the selection of potassium silicate as the main stabilising component and these advantages include the following:

10

- 1) water based fluid which is non-toxic;
- 2) the heaving of shale is prevented;
- 3) the swelling of clays is inhibited, the dispersion of clays is prevented and clay and other weak formations are hardened sufficiently to meet operational requirements; and
- 4) the borehole becomes essentially sealed with a coating by the fluid which can prevent the invasion of filtrate.

15

20

The invention allows re-consideration of accessing soft formation sites previously abandoned due to troublesome working or rejected as too costly to work due to repeated borehole collapse.

25

The fluid of the present invention also tends to repel solids rather than entrain them as observed with prior art such as Darley (US-A-3 640 343).

30

It is notable that the fluid of this invention contains no bentonite or barite or other solids weighting material and is free of brine solutions commonly used in prior art drilling fluids. The fluid of this invention also requires significantly less polymer content than prior formulations yet on the API fluid loss test a fluid loss of zero is achievable.

CLAIMS

1. An aqueous drilling fluid containing a proportion of polymeric agents for fluid loss control and rheological control, and comprising an amount of alkali metal silicate wherein the alkali metal silicate content consists essentially of a range of potassium silicates i.e. containing silica and potassium oxide in various ratios.
2. A fluid according to claim 1 comprising from 28 to 35% by weight of potassium silicate wherein the silica ( $\text{SiO}_2$ ) content is from 20 to 40% by weight and the potassium oxide ( $\text{K}_2\text{O}$ ) content is from 8 to 15% by weight.
3. A fluid according to claim 1 or claim 2 wherein the viscosity of the fluid lies in the range of 35 - 50 mPas at 20 C.
4. A fluid according to claim 1 or claim 2 wherein the fluid loss is below 4 mls on the API fluid loss test.
5. A fluid according to claim 1 or claim 2 wherein the polymeric agents are selected from the group consisting of cellulose based polymers and xanthan gums.
6. A fluid according to claim 1 or claim 2 wherein the amount of polymeric agent providing viscosity control is from 3 to 6  $\text{kg/m}^3$  of fluid.
7. A fluid according to claim 1 or claim 2 wherein the amount of polymeric agent providing fluid loss control is from 1 to 3  $\text{kg/m}^3$  of fluid.
8. A method of drilling and consolidating a borehole in a shale, chalk or similar soft formation wherein during a drilling operation there is introduced an aqueous drilling fluid comprising an amount of alkali metal silicate wherein the alkali metal silicate content consists essentially of a range of potassium silicates, and a proportion of polymeric agents for fluid loss control and rheological control.

9. A method according to claim 6 wherein the fluid contains from 28 to 35% by weight of potassium silicate wherein the silica ( $\text{SiO}_2$ ) content is from 20 to 40% by weight and the potassium oxide ( $\text{K}_2\text{O}$ ) content is from 8 to 15% by weight.

10. A method of producing a drilling fluid comprising providing an aqueous solution of potassium silicate having a selected molar ratio of  $\text{K}_2\text{O}$  to  $\text{SiO}_2$ , adding selected viscosity and fluid loss agents thereto, and adding, in powdered form, predetermined amounts of at least one further potassium silicate of differing molar ratio of  $\text{K}_2\text{O}$  to  $\text{SiO}_2$  from that already in solution to obtain a fluid of a selected density.



# INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 95/00731

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 6 C09K7/02

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 C09K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP,A,0 333 458 (E.I.DU PONT DE NEMOURS) 20 September 1989 cited in the application	1,8
A	see page 4, line 7 - line 28 ---	2
Y	US,A,5 358 044 (A.H.HALE) 25 October 1994 see column 16, line 17 - line 62 ---	1,6-8
Y	US,A,5 361 841 (A.H.HALE) 8 November 1994 see column 16, line 3 - line 52 ---	1,6-8
Y	DATABASE WPI Derwent Publications Ltd., London, GB; AN 92-389283 & SU,A,1 699 991 (MOSC.GUBKIN OIL GAS INST.) see abstract --- -/--	1,5

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

20 March 1996

Date of mailing of the international search report

- 2. 04. 96

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+ 31-70) 340-3016

Authorized officer

Boulon, A

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/IB 95/00731

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	<p>DATABASE WPI Derwent Publications Ltd., London, GB; AN 84-212342 &amp; SU,A,1 063 821 (SOYUZTERMNEFT OIL) see abstract</p> <p style="text-align: center;">---</p>	1,5
Y	<p>DATABASE WPI Derwent Publications Ltd., London, GB; AN 80-89742c &amp; SU,A,730 786 (MOSCOW GUBKIN PETROCHEM) see abstract</p> <p style="text-align: center;">-----</p>	1,5

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB 95/00731

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-333458	20-09-89	US-A- 4988450 CA-A- 1328992 NO-B- 177935	29-01-91 03-05-94 11-09-95
US-A-5358044	25-10-94	NONE	
US-A-5361841	08-11-94	NONE	

BLANK PAGE

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINE(S) OR MARK(S) ON ORIGINAL DOCUMENT**
- ☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

**BLANK PAGE**